

# Beta 3

## 92936723 BETA 3 4100-840 HF E3 LRO Q625

|                           |  |                      |      |  |  |  |  |       |                         |
|---------------------------|--|----------------------|------|--|--|--|--|-------|-------------------------|
| IEC EN<br>60598-1<br>RG 0 |  | <br>↓ IP20<br>↑ IP44 | IK03 |  |  |  |  | 650°C | T <sub>a</sub> 0<br>+25 |
|---------------------------|--|----------------------|------|--|--|--|--|-------|-------------------------|

### Beta 3

A square ceiling recessed LED luminaire. Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Class I electrical, IP44\_IP20, Impact strength: IK03. Body: sheet steel, white (close to RAL9016). Diffuser: Opalised PMMA with micro-prismatic foil inlay. Safety wire not included. Complete with 4000K LED.

UGR < 19 and L65 < 3000 cd/m<sup>2</sup> as per EN 12464

Dimensions: 622 x 622 x 34 mm  
Luminaire input power: 33.6 W  
Luminaire luminous flux: 4100 lm  
Luminaire efficacy: 122 lm/W  
Weight: 3.8 kg



TLG\_BET3\_F\_MREQ.jpg



TLG\_BET3\_M\_Q600.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting