

Punch

96635399 <PUNCH 3 LRO MSP 6600-830 L15 HFIX E3



Punch

A slim, suspended luminaire with direct/indirect distribution. DALI dimmable Electronic, with 3 hour, manual test, emergency lighting circuit. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Light guided via backlit multilayer PMMA LRO luminance reducing optic with UGR <19, closed optical system to prevent damage from electrostatic discharge, ideal for schools and offices. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 3000K LED.

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1542 x 162 x 50 mm
 Luminaire input power: 54.1 W
 Luminaire luminous flux: 6825 lm
 Luminaire efficacy: 126 lm/W
 Weight: 6.8 kg



TLG_PNCH_F_LRO_suspended_on_PDB.jpg



TLG_PNC3_M_PLEXD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Punch

96635399 <PUNCH 3 LRO MSP 6600-830 L15 HFIX E3

THORN