

92943778 CETUS3 M 3000-840 HF E3 RWH

IEC EN 60598-1 RG 1	UK CA	IP20	IP43	halogen	IK03		CE	EAC		850°C	T _a 5 25	
---------------------	-------	------	------	---------	------	--	----	-----	--	-------	---------------------	--

Cetus


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver with 3 hour, manual test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP43_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 4000K LED

For installation in concrete ceilings please contact sales

Dimensions: Ø195 x 100 mm
 Luminaire input power: 27.6 W
 Luminaire luminous flux: 3222 lm
 Luminaire efficacy: 117 lm/W
 Weight: 0.83 kg



TLG_CTU3_F_M_LED_RWH_Persp.jpg



TLG_CTU3_M_HFM.wmf

This product contains a light source of energy efficiency class C.

Cetus

92943778 CETUS3 M 3000-840 HF E3 RWH

THORN