

92943839 CETUS3 L 2000-830 HF E3D RWH

IEC EN 60598-1 RG 1	UK CA	X	IP20 ↑ IP43	halogen	IK03		CE		EAC			850°C	T _a 5 25	
------------------------	----------	---	----------------	---------	------	--	----	--	-----	--	--	-------	------------------------	--

Cetus


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø190-230 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP43_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 3000K LED

For installation in concrete ceilings please contact sales

Dimensions: Ø248 x 100 mm
 Luminaire input power: 15.5 W
 Luminaire luminous flux: 2119 lm
 Luminaire efficacy: 137 lm/W
 Weight: 1.19 kg



TLG_CTU3_F_L_LED_RWH_Persp.jpg



TLG_CTU3_M_HFL.wmf

This product contains a light source of energy efficiency class D.

Cetus

92943839 CETUS3 L 2000-830 HF E3D RWH

THORN