

## 92943850 CETUS3 M 3000-830 HFIX E3D RWH

IEC EN 60598-1 RG 1	UK CA				IK03							850°C	T <sub>a</sub> 5 25	
---------------------------	----------	--	--	--	------	--	--	--	--	--	--	-------	------------------------	--

### Cetus


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, DALI dimmable LED driver with DC functionality, adjustable 15-100%, NFC configurable, SwitchDIM compatible with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP43\_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 3000K LED

For installation in concrete ceilings please contact sales

Dimensions: Ø195 x 100 mm  
Luminaire input power: 26.9 W  
Luminaire luminous flux: 3089 lm  
Luminaire efficacy: 115 lm/W  
Weight: 1.21 kg



TLG\_CTU3\_F\_M\_LED\_RWH\_Persp.jpg



TLG\_CTU3\_M\_HFM.wmf

This product contains a light source of energy efficiency class D.