

92943858 CETUS3 S 800-830 HF E3D RWH

IEC EN 60598-1 RG 1	UK CA			halogen	IK03		CE					850°C	T _a 5 25	
---------------------------	----------	--	--	---------	------	--	----	--	--	--	--	-------	------------------------	--

Cetus


A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø95-125 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP43_IP20. Spring clips suitable for ceiling thicknesses from 1 to 25 mm. Complete with 3000K LED

For installation in concrete ceilings please contact sales

Dimensions: Ø137 x 80 mm
 Luminaire input power: 6.6 W
 Luminaire luminous flux: 758 lm
 Luminaire efficacy: 115 lm/W
 Weight: 0.83 kg



TLG_CTU3_F_S_LED_RWH_Persp.jpg



TLG_CTU3_M_HFS.wmf

This product contains a light source of energy efficiency class D.

Cetus

92943858 CETUS3 S 800-830 HF E3D RWH

THORN