

# Novaline Style

96635535 NOVS M 2500-840 DI HFI BK

THORN

|                           |      |          |    |      |   |         |      |  |    |  |  |  |       |                           |  |
|---------------------------|------|----------|----|------|---|---------|------|--|----|--|--|--|-------|---------------------------|--|
| IEC EN<br>60598-1<br>RG 1 | RoHS | UK<br>CA | 11 | IP54 | D | halogen | IK08 |  | CE |  |  |  | 850°C | T <sub>a</sub> -15<br>+25 |  |
|---------------------------|------|----------|----|------|---|---------|------|--|----|--|--|--|-------|---------------------------|--|

## Novaline Style

Decorative circular luminaire with medium body. Low indirect component for wall and ceiling illumination. Electronic, DALI dimmable. Aesthetic trim of the luminaire made of polycarbonate in black. Diffuser: opal polycarbonate. Class II electrical, IP54. Complete with 4000K LED.

Dimensions: Ø397 x 69 mm  
Luminaire input power: 17.6 W  
Luminaire luminous flux: 2500 lm  
Luminaire efficacy: 142 lm/W  
Weight: 2.14 kg



TLG\_NOVS\_F\_4BK.jpg



TLG\_NOVS\_M\_LD400.wmf

This product contains a light source of energy efficiency class C.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting