## **Victor**



## 96635797 VIC2 48L35-740 NR CL2 N8M R9006



## Victor


A large size LED road and street luminaire, in a modern and timeless design. 48 LEDs driven at 350mA with Narrow Road optic. Fixed output LED driver. Class II electrical, IP66. Body in aluminium, powder coated White aluminium RAL9006. Enclosure: toughened glass. Luminaire to be suspended using brackets (Ø27G), post top, or wall mounted. Tool-free electrical connection via 2 x 2.5 mm<sup>2</sup> terminal block. Pre-wired with 8m H07-RNF cable. Complete with 4000K LED

Dimensions: Ø503 x 360 mm Luminaire input power: 51 W

Weight: 8.42 kg Scx: 0.144 m<sup>2</sup>



TLG VCTR F 65PDB.jpg



TLG\_VCTR\_M\_SWLD2.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

## **Victor**



96635797 VIC2 48L35-740 NR CL2 N8M R9006