

THORN

Technical specifications and certifications for the LED strip light:

- CB Certificate
- ISO 9223 C5
- UKCA
- EN
- IP66
- IK08
- Grounding symbol
- CE
- RoHS symbol
- Energy efficiency symbol (A)
- Dimmable symbol
- 0,5m

A compact, lightweight, general purpose LED area floodlight. With small body. LED converter driving 24 LEDs at 500mA with Asymmetrical 40° light distribution. IP66, IK08, Class I electrical. Body: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006).. Enclosure: 4mm thick toughened glass. Reversible mounting stirrup supplied, optional spigot adaptors available separately for post top mounting. Complete with 4000K LED.

Dimensions: 429 x 349 x 99 mm
 Luminaire input power: 37 W
 Luminaire luminous flux: 6071 lm
 Luminaire efficacy: 164 lm/W
 weight: 6.79 kg
 Scx: 0.052 m²



This product contains a light source of energy efficiency class D.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Areaflood Pro 2

96635900 AFP2 S 24L50-740 A4 CL1 GY

THORN