

## GTLED Pro gears polyester

### Light that lasts - for any tunnel

- Designed for long lasting performance suitable with the highest corrosion classification (C5) and no debris retention design
- Light in weight, easy to handle, flexible in fixation - the gear box can be installed up to 200m away from the luminaire to offer safe installation and maintenance
- One single gear box can feed up to 20 luminaires for optimization of the material installed and reduction of the structure constraints
- Dimming on the control gear possible via DALI or Pilot Line
- Pre-wired with connector for a fast error free plug to the luminaire
- Through wiring ready for loop-in loop-out between gear boxes without the need for additional junction box



Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.

### Material/Finish

Body: polyester glass reinforced (25%)

Brackets: steel 316L

Finish: unpainted polyester light grey

### Installation/Mounting

Fixation onto the structure (e.g. ladder) via 2 brackets (supplied) by the means of screws (not supplied)

Power in cabling via one dedicated cable gland - power out (through wiring) via another dedicated cable gland

DALI in cabling via one dedicated cable gland - DALI out via another dedicated cable gland

Ready to plug to the luminaire with the pre-wired and fitted corresponding connector

### Ordering Guide

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
<b>GTLED Pro, gear box, plastic</b>				
GP PB 2X135 DA HV-OUT1 70 W1,5 CL1			6,697	96668861
GP PB 3X200 DA HV-OUT1 85 W1,5 CL1			8,612	96669921
GP PB 4X135 DA HV-OUT2 70 W1,5 CL1			9,229	96669922
GP PB 4X135 DA HV-OUT2 50 W1,5 CL1			9,229	96670013
GP PB 1X200 DA LV-OUT1 100 W1,5 CL1			5,711	96670003
GP PB 1X200 DA LV-OUT1 105 W1,5 CL1			5,711	96668849
GP PB 1X200 DA LV-OUT1 50 W1,5 CL1			5,711	96668852
GP PB 1X200 DA LV-OUT1 70 W1,5 CL1			5,711	96668854
GP PB 1X200 DA LV-OUT1 85 W1,5 CL1			5,711	96670004
GP PB 2X135 DA HV-OUT1 50 W1,5 CL1			6,697	96668859
GP PB 2X135 DA LV-OUT1 105 W1,5 CL1			6,697	96668856
GP PB 2X135 DA LV-OUT2 100 W1,5 CL1			6,844	96670005
GP PB 2X200 DA HV-OUT1 50 W1,5 CL1			7,147	96668871
GP PB 2X200 DA HV-OUT1 70 W1,5 CL1			7,147	96668873
GP PB 2X200 DA LV-OUT1 85 W1,5 CL1			7,147	96670008
GP PB 2X200 DA LV-OUT2 100 W1,5 CL1			7,294	96670007
GP PB 2X200 DA LV-OUT2 105 W1,5 CL1			7,294	96668875
GP PB 3X200 DA HV-OUT1 70 W1,5 CL1			8,612	96670010
GP PB 4X135 DA LV-OUT2 105 W1,5 CL1			9,229	96670012
GP PB 4X200 DA HV-OUT2 70 W1,5 CL1			10,129	96670017